OLD DOMINION FREIGHT LINE, INC.

BILL OF LADING API DEVELOPMENT GUIDE





© 2025 Old Dominion Freight Line, Inc. Thomasville, N.C. All rights reserved.

Contents

| Getting Started | 1 |
|------------------------|----|
| Overview | 1 |
| Testing | 1 |
| Authentication | 2 |
| Bearer Token | 2 |
| Request | 3 |
| Authorization | 3 |
| Base Path | 3 |
| Create & Modify Fields | 4 |
| Values | 14 |
| Response | 23 |
| Fields | 23 |
| Flags | 24 |
| Values | 24 |
| Sample | 25 |
| Request | 25 |
| Response | 29 |

Getting Started

Overview

The eBOL Standard API is a REST service for submitting electronic Bills of Lading. It follows the NMFTA's digital council eBOL format and supports data sharing with OD and any carrier using the standardized eBOL. The API connects to our billing system, enabling the creation of shipping labels and Bills of Lading. Users can either receive a PRO number or provide one they already have. After submission, users can also modify the eBOL data.

For more information on all our API services, visit the Shipping API Integrations Page at ODFL.com.

Testing

We offer a QA environment for onboarding and testing purposes. To get started, visit the <u>Shipping API Integrations Page</u> and click "<u>Email an Expert</u>" for help.

Authentication

To use this service, you need an ODFL.com account with a username and password. This will give you access to your account data. To register, visit <u>ODFL.com</u> and click "<u>Sign Up</u>".

If you have questions about your OD account, we're available to help Monday-Friday, 7 a.m.-8 p.m. ET.

• Telephone: 1-800-235-5569

• Email: Internet.CustomerService@odfl.com

Bearer Token

Request

Obtain a session token by making a GET request to:

| Environment | URL |
|-------------|---------------------------------------|
| QA | https://apiq.odfl.com/auth/v1.0/token |
| Production | https://api.odfl.com/auth/v1.0/token |

Authorization Type: Basic Auth

Username: Provide your ODFL.com Username

Password: Provide your ODFL.com Password

Response

| Code | Message | Notes |
|------|---------------------|--|
| 200 | ОК | A session token and expiration are returned. Session tokens expire one hour after issue. |
| 400 | Invalid Credentials | The OD Username or Password you've provided is incorrect or your account is disabled. Contact API@odfl.com for assistance. |
| 503 | Service Unavailable | Verify that the URL and Authorization Type is correct. If the problem persists, please notify us at API@odfl.com . |

Request

Authorization

Utilize the session token obtained during Authentication as Authorization.

• Type: Bearer Token

Base Path

Create

Perform a POST to:

| Environment | URL |
|-------------|--|
| QA | https://apiq.odfl.com/BOL/v3.1/eBOL/bol-external-per-standards |
| Production | https://api.odfl.com/BOL/v3.1/eBOL/bol-external-per-standards |

Modify

Can only be done for pros that have had eBoL data submitted by create.

Perform a PUT to:

| Environment | URL |
|-------------|---|
| QA | https://apiq.odfl.com/BOL/v3.1/eBOL/modify-bol-external-per-standards |
| Production | https://api.odfl.com/BOL/v3.1/eBOL/modify-bol-external-per-standards |

Delete

Send the pro number to be deleted as a parameter on this endpoint. There is no body for this request.

Perform a DELETE to:

| Environment | URL |
|-------------|---|
| QA | https://apiq.odfl.com/BOL/v3.1/eBOL/deleteBolPro?proNumber= |
| Production | https://api.odfl.com/BOL/v3.1/eBOL/deleteBolPro?proNumber= |

Create & Modify Fields

Required

| Name | Туре | Description |
|--|--------------|--|
| bol.requestedPickupDate | ISO- 8601 | The requested pickup date -"2025-01-15" or "2025-01-15T10:30:00.000" -YYYY-MM-DD or YYYY-MM-DDTHH:mm:ss.sss -Value in PickupDate does not generate a pickup requestUse our Pickup API to request pickup. |
| bol.function | String | The intent for the submitted request. (See <u>Values</u>) |
| bol.isTest | Boolean | The value should always be 'False' when calling to the production environmentUse OD's QA environment instead of 'True'. |
| bol.requestorRole | String | Identifies the party making the request. (See <u>Values</u>) |
| version | String | Which minor version of the Digital LTL Council Bill of Lading spec being used 2.1.0 |
| commodities.lineItemLayout | String | The layout of the commodities shipped. (See <u>Values</u>) |
| commodities.handlingUnits.count | Integer | Number of the handling units being described. |
| commodities.handlingUnits.type | String | Types of the handling units being described. (See <u>Values</u>) |
| commodities.handlingUnits.weight | Integer | Total weight for the specified handling units. |
| commodities.handlingUnits.lineItems.d escription | String | Description of the freight. |
| commodities.handlingUnits.lineItems.w eight | Integer | Total weight for the specified line Item. |
| commodities.handlingUnits.lineItems.pi eces | Integer | Number of individual pieces for the line item being described. |
| commodities.handlingUnits.lineItems.p ackagingType | String | Packaging type for the individual pieces of the line item being described. (See <u>Values</u>) |
| commodities.handlingUnits.lineItems.cl assification | String | The shipment item class. (See_ <u>Values</u>) |
| commodities.handlingUnits.lineItems.h azardous | Boolean | Indicates whether the shipment is hazardous materialsTrue or false |
| payment.terms | String | The freight payment terms (See <u>Values</u>) |
| origin.name | String | Company name associated with the origin location |
| origin.address1 | String | Line1 of the origin location address |

| Name | Type | Description |
|---------------------------|--------|--|
| origin.city | String | City of the origin location address |
| origin.stateProvince | String | Two letter state/province code for the origin location address. |
| origin.postalCode | String | The address zip/postal code of the origin location"12345-1234" (5 digits + 4 - USA) -"12345" (5 digits - USA/MEX) -"A1A1A1" (6 characters - CAN) -"A1A1A" (5 characters - CAN) |
| origin.country | String | Three letter country code for the origin location. (See <u>Values</u>) |
| origin.contact.phone | String | The origin telephone number -"9995551212" 10 digits (Area code + phone) |
| destination.name | String | Company name associated with the destination location. |
| destination.address1 | String | Line1 of the destination location address. |
| destination.city | String | City of the destination location address. |
| destination.stateProvince | String | Two letter state/province code for the destination location. |
| destination.postalCode | String | The address zip code of the destination location"12345-1234" (5 digits + 4 - USA) -"12345" (5 digits - USA/MEX) -"A1A1A1" (6 characters - CAN) -"A1A1A" (5 characters - CAN) |
| destination.country | String | Three letter country code for the destination locati on. (See <u>Values</u>) |
| destination.contact.phone | String | The destination telephone number -"9995551212" 10 digits (Area code + phone) |
| billTo.name | String | Company name associated with the billTo location |
| billTo.address1 | String | Primary Address line for the billTo location. |
| billTo.city | String | City Name for the billTo location. |
| billTo.stateProvince | String | Two letter state/province code for the billTo location. |
| billTo.postalCode | String | The address zip code of the billTo location"12345-1234" (5 digits + 4 - USA) -"12345" (5 digits - USA/MEX) -"A1A1A1" (6 characters - CAN) -"A1A1A" (5 characters - CAN) |
| billTo.country | String | Three letter country code for the billTo location. (See <u>Values</u>) |

| Name | Туре | Description |
|----------------------|--------|---|
| billTo.contact.phone | String | The billTo telephone number"9995551212" 10 digits (Area code + phone) |

Conditionally Required

| Name | Туре | Description |
|---|---------|---|
| images.shippingLabels.format | String | Specifies the printer format type for the labelsRequired when images.includeShippingLabels is trueAvery or Zebra |
| images.shippingLabels.quantity | Integer | Specifies the quantity of pages desiredRequired when images.includeShippingLabels is true. |
| images.shippingLabels.position | Integer | Specifies the starting position for shipping labelsRequired when images.shippingLabel is AveryValid Values: 1-6 |
| images.email.addresses | Array | Provide one or more email addresses to receive the bol and/or shipping labels PDFRequired when images.email.includeBoL and/or images.email.includeLabels is true |
| commodities.handlingUnits.lineItems.h azardousDescription | String | Detailed description of the hazardous item Required when hazardous flag is true - "UN/NA#, Proper Name, (Technical Name if applicable), Hazardous Class, Packing Group if applicable" |
| commodities.handlingUnits.lineItems.h azardousDetails.weight | Integer | Total weight of hazardous material covered by one description Required when hazardous flag is true |
| commodities.handlingUnits.lineItems.h azardousDetails.class | String | Hazardous material class Required when hazardous flag is true |
| commodities.handlingUnits.lineItems.h azardousDetails.unnaNumber | String | Indicates Proper Identification Number (UN or NA) corresponding to the Proper Shipping Name Required when hazardous flag is true -UN or NA followed by 4 digits |
| commodities.handlingUnits.lineItems.h azardousDetails.propername | String | Proper shipping name of the hazardous material Required when hazardous flag is true |
| commodities.handlingUnits.lineItems.h azardousDetails.technicalName | String | Technical name for the hazardous material. - DOT requirement if applicable -Not all hazardous items will have a technical name. |
| commodities.handlingUnits.lineItems.h azardousDetails.packingGroup | String | Hazmat Packing Group numberDOT requirement if applicable -Not all hazmat items have a packing group. |
| commodities.handlingUnits.lineItems.h azardousDetails.contractNumber | String | The contract number of the hazardous materials DOT requirement if applicable |
| accessorials.codes | Array | The list of services requested for the shipment. (See <u>Values</u>) |

| Name | Туре | Description |
|--|---------|--|
| accessorials.hazardousDetails.emerge ncyContact.name | String | Name of the contact person in case of hazardous materials-related issue Required when hazardous flag is true |
| accessorials.hazardousDetails.emerge ncyContact.phone | String | Phone number of the contact person in case of hazardous materials-related issue Required when hazardous flag is true - "9995551212" 10 digits (Area code + phone) |
| accessorials.cod.amount | String | Amount to be received for the CODRequired when accessorial code COD is present in the accessorial.codes listOD does not support COD. |
| accessorials.cod.currency | String | Optional attribute to indicate currency of COD. (See <u>Values</u>) -Required when accessorial code COD is present in the accessorial codes listDefaults to USD -OD does not support COD. |
| accessorials.cod.terms | String | Payment terms associated with the COD. (See Values) -Required when accessorial code COD is present in the accessorial.codes listOD does not support COD. |
| accessorials.cod.customerCheckAccep table | Boolean | Indicates if a customer check or cash is acceptableRequired when accessorial code COD is present in the accessorial codes listTrue or false -OD does not support COD. |
| accessorials.cod.remitTo.name | String | Name of the remit to companyRequired when accessorial code COD is present in the accessorial codes listOD does not support COD. |
| accessorials.cod.remitTo.address1 | String | Primary Address line of the remit to companyRequired when accessorial code COD is present in the accessorial.codes listOD does not support COD. |
| accessorials.cod.remitTo.address2 | String | Secondary Address of the remit to companyRequired when accessorial code COD is present in the accessorial.codes listOD does not support COD. |
| accessorials.cod.remitTo.city | String | City Name of the remit to companyRequired when accessorial code COD is present in the accessorial.codes listOD does not support COD. |
| accessorials.cod.remitTo.stateProvince | String | Two letter state/province code of the remit to company. |

| Name | Туре | Description |
|---|--------------|---|
| Continued- accessorials.cod.remitTo.stateProvince | | -Required when accessorial code COD is present in the accessorial codes listOD does not support COD. |
| accessorials.cod.remitTo.postalCode | String | The address zip code of the of the remit to companyRequired when accessorial code COD is present in the accessorial codes listOD does not support COD. |
| accessorials.cod.remitTo.country | String | Three letter country code of the remit to company. (See <u>Values</u>) -Required when accessorial code COD is present in the accessorial codes listOD does not support COD. |
| accessorials.sortAndSegregate Details.pieces | Integer | Number of pieces in a shipment to be sorted and segregatedRequired when accessorial code SRT is present in the accessorial.codes list. |
| accessorials.fullValueCoverageDetails. monetaryValue | String | Value of the cargo -Required when accessorial code FVC is present in the accessorial.codes list"500.50" (2 decimal places only) |
| accessorials.fullValueCoverageDetails.currency | String | Optional attribute to indicate currency of monetary value. (See <u>Values</u>) -Required when accessorial code FVC is present in the accessorial.codes listDefaults to USD |
| accessorials.markDetails.pieces | Integer | Number of pieces in a shipmentRequired when accessorial code MARK is present in the accessorial.codes list. |
| accessorials.limitedAccessType.origin | String | To indicate the limited access type at the origin when accessorial code LTDAP is present. (See Values) -Required when accessorial code LTDAP is present in the accessorial.codes list. |
| accessorials.limitedAccessType.destin ation | String | To indicate the limited access type at the destination when accessorial code LTDAD is present. (See Values) -Required when accessorial code LTDAD is present in the accessorial.codes list. |
| accessorials.timeCriticalDetails.type | String | To indicate type of delivery "Time Critical Service" (See Values) -Required when accessorials.code list include TCS. |
| accessorials.timeCriticalDetails.date.st art | ISO- 8601 | The start date (with or without time) of the requested delivery windowRequired when accessorials.code list include TCS. |

| Name | Type | Description |
|--|--------------|--|
| | | -"2025-01-15" <u>or</u> "2025-01-15T10:30:00.000" -YYYY-MM-DD <u>or</u> YYYY-MM-DDTHH:mm:ss.sss |
| accessorials.timeCriticalDetails.date.en d | ISO- 8601 | The end date (with or without time) of the requested delivery windowRequired when accessorials.code list include TCS"2025-01-15" or "2025-01-15T10:30:00.000" -YYYY-MM-DD or YYYY-MM-DDTHH:mm:ss.sss |
| accessorials.appointmentDetails.picku p.start | ISO- 8601 | The start date (with or without time) of the requested shipment pickup windowRequired when accessorials.code list include APTP"2025-01-15" or "2025-01-15T10:30:00.000" -YYYY-MM-DD or YYYY-MM-DDTHH:mm:ss.sss |
| accessorials.appointmentDetails.picku p.end | ISO- 8601 | The end date (with or without time) of the requested shipment pickup windowRequired when accessorials.code list include APTP"2025-01-15" or "2025-01-15T10:30:00.000" -YYYY-MM-DD or YYYY-MM-DDTHH:mm:ss.sss |
| accessorials.appointmentDetails.delive ry.start | ISO- 8601 | The start date (with or without time) of the requested shipment pickup windowRequired when accessorials.code list include APTD"2025-01-15" or "2025-01-15T10:30:00.000" -YYYY-MM-DD or YYYY-MM-DDTHH:mm:ss.sss |
| accessorials.appointmentDetails.delive ry.end | ISO- 8601 | The end date (with or without time) of the requested shipment pickup windowRequired when accessorials.code list include APTD"2025-01-15" or "2025-01-15T10:30:00.000" -YYYY-MM-DD or YYYY-MM-DDTHH:mm:ss.sss |
| customsBroker.contact.phone | String | The Customs Broker telephone numberRequired when adding customsBroker -"9995551212" 10 digits (Area code + phone) |

Optional

| Name | Туре | Description |
|------------------------------|---------|---|
| bol.specialInstructions | String | Special delivery instructions that need to be followed for the shipment's deliveryInstructions included here will be printed on the Bill of Lading. |
| images.includeBol | Boolean | Indicates whether the image of the populated BOL should be returned in the response. -True or false -Default is false |
| images.includeShippingLabels | Boolean | Indicates whether the image(s) of the shipping labels should be returned in the response. -True or false -Default is false |

| Name | Туре | Description |
|-----------------------------|---------|--|
| images.email.includeBol | Boolean | Indicates to send the BOL PDF to be sent to one or more email addresses. -True or false |
| images.email.includeLabels | Boolean | Indicates to send the shipping labels PDF to be sent to one or more email addresses. -True or false |
| notifications.phoneNumber | String | Phone number of the contact for tracking updates about shipment movements. |
| notifications.email | String | Email address of the contact for tracking updates about shipment movements. |
| referenceNumbers.pro | String | Shipper's pre-assigned PRO number for the requested carrierIf pro is not provided, one will be auto assigned by the carrierIf sent but has no value, send as null |
| referenceNumbers.quoteld | String | Quote (estimate) number provided by the carrier after submitting a rate quote request. -Value should not contain a tariff prefix and/or hyphen10 digits -If sent but has no value, send as null |
| referenceNumbers.shipmentId | String | Shipment ID (SID) number for the shipmentIf sent but has no value, send as null |
| referenceNumbers.masterBol | String | Master Bill of Lading number for the shipmentIf sent but has no value, send as null |
| referenceNumbers.trailerId | String | Indicates the spotted trailer a shipment is loaded onIf sent but has no value, send as null |
| referenceNumbers.manifestId | String | Indicates that the shipment is associated to a manifest that includes multiple shipments, possibly across multiple spotted trailersIf sent but has no value, send as null |
| referenceNumbers.bol | Array | An array to contain bill of lading numbersValues in the array should be stringsMultiple BOL numbers can be sent. |
| referenceNumbers.po | Array | An array to contain purchase order numbers and information related to those numbers. |
| referenceNumbers.po.number | String | The Purchase Order numberMultiple PO numbers can be sent. |
| referenceNumbers.po.pieces | Integer | Total pieces associated with the Purchase Order. |
| referenceNumbers.po.weight | Integer | Total weight associated with the Purchase Order. |

| Name | Туре | Description |
|--|---------|--|
| referenceNumbers.po.weightUnit | String | The unit of measurement for weight. Defaults to Pounds (Imperial) if not passed. (See <u>Values</u>) |
| referenceNumbers.po.palletized | Boolean | Indicates whether the pieces associated with the purchase order numbers are on a pallet/slip/skid or not. -True or false |
| referenceNumbers.po.additional ShipperInfo | String | Additional information from shipper per line item |
| referenceNumber.additionalReferences .name | String | Indicates the specific user type and/or type. (See Values) -Does not appear on OD BOL document. |
| referenceNumber.additionalReferences .value | String | Indicates the name of the specific userLOAD will be the only value displayed on OD BOL document. |
| commodities.handlingUnits.tareWeight | Integer | Weight of the skids/pallets/slips used in the shipment |
| commodities.handlingUnits.stackable | Boolean | Identifies if the freight can be stacked on one anotherTrue or false -Default is false -Must be false if lineItems.hazardous is true |
| commodities.handlingUnits.weightUnit | String | The unit of measurement for weight. (See <u>Values</u>) -Defaults to Pounds (Imperial) if not passed. |
| commodities.handlingUnits.length | String | The length of the handling units being described. |
| commodities.handlingUnits.width | String | The width of the handling units being described. |
| commodities.handlingUnits.height | Integer | The height of the handling units being described. |
| commodities.handlingUnits.dimensions Unit | String | The unit of measurement for dimensions. (See <u>Values</u>) -Defaults to Inches (Imperial) if not passed. |
| commodities.handlingUnits.lineItems.w eightUnit | String | The unit of measurement for weight. (See <u>Values</u>) -Defaults to Pounds (Imperial) if not passed. |
| commodities.handlingUnits.lineItems.n mfc | String | The handling unit NMFC code of the freight. |
| commodities.handlingUnits.lineItems.n mfcSub | String | The handling unit NMFC sub value of the freight. |
| shipmentTotals.grossWeight | Integer | Total weight of the entire shipment, including handling units (tare weight). |
| shipmentTotals.netWeight | Integer | Total weight of the entire shipment, not including handling units (tare weight). |

| Name | Туре | Description |
|-----------------------------------|---------|--|
| shipmentTotals.weightUnit | String | The unit of measurement for weight. (See <u>Values</u>) -Defaults to Pounds (Imperial) if not passed. |
| shipmentTotals.handlingUnits | Integer | Handling unit count for the entire shipment. |
| shipmentTotals.linearLength | Integer | Linear length for the entire shipment |
| shipmentTotals.dimensionsUnit | String | The unit of measurement for dimensions. (See Values) -Defaults to Inches (Imperial) if not passed. |
| shipmentTotals.cube | Integer | Cubic volume of the entire shipmentTotal length X total width X total height |
| shipmentTotals.cubeDimensionsUnit | String | The unit of measurement for cubic dimensions. (See Values) -Defaults to Feet (Imperial) if not passed. |
| shipmentTotals.declaredValue | Integer | Total monetary value of the shipment in USD |
| shipmentTotals.currency | String | Indicates monetary value of the shipment. (See Values) -Defaults to USD. |
| origin.account | String | Company's OD account number/id for the origin. |
| origin.locationID | String | Company's locationId for the originOD does not support this feature. |
| origin.address2 | String | Secondary Address line for the origin location. |
| origin.contact.phoneExt | String | The origin telephone extension. |
| origin.contact.name | String | Name of the origin location's contact person. |
| origin.contact.email | String | Email address of the origin location's contact person. |
| destination.account | String | Company's OD account number/id for the destination. |
| destination.locationID | String | Company's locationID for the destinationOD does not support this feature |
| destination.address2 | String | Secondary Address line for the destination location |
| destination.contact.phoneExt | String | The destination telephone extension. |
| destination.contact.name | String | Name of the destination location's contact person. |
| destination.contact.email | String | Email address of the destination location's contact person. |
| billTo.account | String | Company's OD account number/id for the billTo. |
| billTo.locationID | String | Company's locationID for the billToOD does not support this feature |

| Name | Туре | Description |
|--------------------------------|--------|--|
| billTo.address2 | String | Secondary Address line for the billTo location. |
| billTo.contact.phoneExt | String | The billTo telephone extension. |
| billTo.contact.name | String | Name of the billTo location's contact person. |
| billTo.contact.email | String | Email address of the billTo location's contact person. |
| customsBroker.type | String | Used to identify a customs broker that is involved in a cross-border freight move. (See <u>Values</u>) |
| customsBroker.name | String | Company name associated with the customs Broker location. |
| customsBroker.address1 | String | Primary Address line for the customs Broker location |
| customsBroker.address2 | String | Secondary Address line for the customs Broker location. |
| customsBroker.city | String | City Name for the customs Broker location |
| customsBroker.stateProvince | String | Two letter state/province code for the customs Broker location. |
| customsBroker.postalCode | String | The address zip/postal code of the Customs Broker location"12345-1234" (5 digits + 4 - USA) -"12345" (5 digits - USA/MEX) -"A1A1A1" (6 characters - CAN) -"A1A1A" (5 characters - CAN) |
| customsBroker.country | String | Three letter country code for the customs Broker location. (See <u>Values</u>) |
| customsBroker.contact.phoneExt | String | The Customs Broker telephone extension. |
| customsBroker.contact.name | String | Broker location's contact person. |
| customsBroker.contact.email | String | Email address of the customs |

Values

| Field Name | Valid Values | Description | |
|--|--------------------------|---|--|
| | Create | | |
| function | Modify | | |
| | Shipper | | |
| requestorRole | Consignee | | |
| | Third Party | | |
| commodities.lineItemLayout | Nested | Indicates if the handlingUnit / lineItem relationship is known. If this value is used, each lineItem associated to a handlingUnit is conditionally required to be passed within that handlingUnit object. | |
| | Stacked | Indicates if the handlingUnit / lineItem relationship is not known. If this value is used, lineItem maybe passed within any handlingUnit object. | |
| | CAN | Canada | |
| Country | MEX | Mexico | |
| | USA | United States | |
| | Deliver On Date | | |
| accessorials timeCriticalDetails type | Deliver On or After Date | | |
| accessorials.timeCriticalDetails.type | Deliver By Date | | |
| | Delivery Window | | |
| | 50 | | |
| | 55 | | |
| | 60 | | |
| | 65 | | |
| commodities.handlingUnits. lineItems.classification | 70 | | |
| interterns.classification | 77.5 | | |
| | 85 | | |
| | 92.5 | | |
| | 100 | | |
| | 110 | | |

| Field Name | Valid Values | Description |
|-------------------------------------|---|--|
| | 125 | |
| | 150 | |
| | 175 | |
| | 200 | |
| | 250 | |
| | 300 | |
| | 400 | |
| | 500 | |
| | Not Required | |
| | Prepaid | Shipper is paying for the freight |
| | Collect | Consignee is paying for the freight |
| payment.Terms | Third Party -OD does not support "Third Party" as a payment term. | If the third party is associated to the shipper, send prepaid with the third party information in the billTo sections. If the third party is associated to the consignee, send collect with the third party information in the billTo sections. If the shipment is a true third party, send either prepaid or collect with the third party information in the billTo sections. |
| commodities.handlingUnits.type, | BAG | Bag |
| commodities.handlingUnits.lineItems | BAL | Bale |
| .packagingType | BBL | Barrel |
| | BSK | Basket |
| | BIN | Bin |
| | вох | Вох |
| | BXT | Bucket |
| | всн | Bunch |
| | BDL | Bundle |
| | САВ | Cabinet |
| Continued- | CAG | Cage |
| commodities.handlingUnits.type, | CAN | Can |

| Field Name | Valid Values | Description |
|--------------------------------------|--------------|-----------------------------|
| commodities handling Inits lineItems | CBY | Carboy |
| | CAR | Carrier |
| | CTN | Carton |
| | CAS | Case |
| | CSK | Cask |
| | CHS | Chest |
| | COL | Coil |
| | CNT | Container |
| | COR | Cores |
| | CRT | Crate |
| | CYL | Cylinder |
| | DRM | Drum |
| | DBK | Dry Bulk |
| | ENV | Envelope |
| | FIR | Firkin |
| | GLD | Gaylord |
| | HGH | Hogshead |
| | HPR | Hamper |
| | HRB | On Hanger or Rack in Boxes |
| | INT | Intermediate Bulk container |
| | JAR | Jar |
| | JCN | Jerrycan |
| | KEG | Keg |
| | KIT | Kit |
| | LIF | Lifts |
| | LBK | Liquid Bulk |
| | LSE | Loose |
| | MXD | Mixed |
| Continued- | ОТН | Other |

| Field Name | Valid Values | Description | |
|-------------------------------------|--------------|-------------------------------|--|
| | PKG | Package | |
| commodities.handlingUnits.type, | PCK | Packed | |
| commodities.handlingUnits.lineItems | PAL | Pail | |
| .packagingType | PAT | Pallet | |
| | PCS | Piece | |
| | PLN | Pipe Line | |
| | RCK | Rack | |
| | REL | Reel | |
| | ROL | Roll | |
| | SKD | Skid | |
| | SLP | Slip Sheet | |
| | SPL | Spool | |
| | TNK | Tank | |
| | TBN | Tote | |
| | TRY | Tray | |
| | TRU | Truckload | |
| | TRK | Trunk | |
| | TUB | Tub | |
| | TBE | Tube | |
| | UNT | Unit | |
| | VPK | Van Pack | |
| | WRP | Wrapped | |
| weightUnit | Pounds | | |
| Weightonit | Kilograms | | |
| dimensionsUnit | Inches | | |
| differisionsoffic | Centimeters | | |
| shipmentTotals.cubeDimensionsUnit | Feet | | |
| | Meters | | |
| additionalReferences.name | Customer | Recommended for Auto Billing. | |

| Field Name | Valid Values | Description |
|-------------------------------------|-----------------|--|
| | Integration | Recommended for Auto Billing. |
| | TMS | If applicable, recommended for Auto Billing. |
| | 3PL | If applicable, recommended for Auto Billing. |
| | LOAD | |
| ahinmantTatala auhaDimanajanal Init | Feet | |
| shipmentTotals.cubeDimensionsUnit | Meters | |
| | Airport | |
| | Airport-3 | Airport Cargo |
| | Church | |
| | Church-55 | Place of Worship |
| | Club | |
| | Club-21 | Country Club / Golf Course |
| | Club-60 | Private Club |
| | Construction | |
| | Construction-17 | Construction Site |
| | Fair | |
| | Fair-27 | Fairgrounds |
| limitedAccessType | Farm | |
| | Farm-30 | Fruit Orchard |
| | Farm-62 | Pumpkin Patch / Vegetable Patch |
| | Farm-87 | Winery |
| | Hotel | |
| | Hotel-14 | Casino |
| | Hotel-35 | Hotel |
| | Hotel-41 | Lodging |
| | Hotel-47 | Motel / Inn |
| | Hotel-54 | Parking Lot / Garage |
| | Hotel-65 | Resort |
| | Hotel-66 | Restaurant / Bar |

| Field Name | Valid Values | Description |
|------------|--------------|-----------------------------|
| | Mine | |
| | Mine-46 | Mine / Quarry |
| | Other | |
| | Other-6 | Book Store |
| | Other-7 | Bowling Alley |
| | Other-8 | Brewery |
| | Other-9 | Business Park |
| | Other-12 | Car Rental |
| | Other-13 | Car Wash |
| | Other-19 | Convenience Store |
| | Other-23 | Daycare |
| | Other-24 | Dealership |
| | Other-25 | Distillery |
| | Other-26 | Factory Outlet |
| | Other-28 | Fast Food |
| | Other-31 | Funeral Home |
| | Other-33 | Gym / Fitness Center |
| | Other-38 | Laundry / Dry Cleaner |
| | Other-40 | Liquor Store |
| | Other-42 | Mall |
| | Other-48 | Native American Reservation |
| | Other-52 | Other |
| | Other-67 | Retail Store |
| | Other-68 | Salon / Barber |
| | Other-72 | Shopping Center |
| | Other-75 | Specialty Food Store |
| | Other-78 | Theater |
| | Other-80 | Truck Stop |
| | Other-83 | Vet / Kennel |

| Field Name | Valid Values | Description |
|------------|--------------|--------------------------------|
| | Park | |
| | Park-4 | Amusement Park |
| | Park-5 | Aquarium |
| | Park-10 | Camp |
| | Park-11 | Campground / RV Park |
| | Park-15 | Cemetery |
| | Park-53 | Park |
| | Park-64 | Recreational |
| | Park-73 | Ski Resort |
| | Park-76 | Sports Venue |
| | Park-77 | State / National Park |
| | Park-88 | Zoo |
| | Port | |
| | Port-22 | Cruise Line Terminal |
| | Port-29 | Ferry |
| | Port-43 | Marina |
| | Port-57 | Port |
| | School | |
| | School-34 | Hospital |
| | School-36 | Junior College |
| | School-39 | Library / Museum |
| | School-44 | Medical Facility |
| | School-50 | Nursing Home / Assisted Living |
| | School-56 | Police / Fire / Rescue |
| | School-61 | Public Transit Station |
| | School-69 | School |
| | School-70 | School District Office |
| | School-79 | Trade School |
| | School-81 | University / College |

| Field Name | Valid Values | Description |
|-------------------|--------------|--|
| | Secure | |
| | Secure-32 | Government Site |
| | Secure-37 | Junkyard / Landfill |
| | Secure-45 | Military Base |
| | Secure-49 | Nuclear Power Plant |
| | Secure-51 | Oil / Gas |
| | Secure-58 | Power Plant |
| | Secure-59 | Prison / Detention Center |
| | Secure-63 | Rail Yard |
| | Secure-74 | Solar Power Farm |
| | Secure-82 | Utility Site |
| | Secure-84 | Waste Transfer Station |
| | Secure-85 | Water Treatment Plant |
| | Secure-86 | Wind Power Farm |
| | Storage | |
| | Storage-18 | Container Freight Station |
| | Storage-71 | Self Storage Warehouse |
| | Tradeshow | |
| | Tradeshow-16 | Conference Center |
| | Tradeshow-20 | Convention Center |
| | APTD | Appointment required at delivery |
| | APTP | Appointment required at pickup |
| | BRO | ODFL Brokerage Service Requested - Delivering Soon -Specific for ODFL use only |
| accessorial.codes | COD | Collect on deliveryODFL does not support COD. |
| | EXPD | Expedited Service |
| | FVC | ODFL Additional Cargo Liability Coverage |
| | GTD_AM | Guaranteed Service -by Morning -OD does not support GTD_AM |

| Field Name | Valid Values | Description |
|------------|--------------|---|
| | GTD_NOON | Guaranteed Service -by Noon |
| | GTD_PM | Guaranteed Service- by End of Day |
| | HAD | Hold at Destination Dock - Delivering Soon -Specific for ODFL use only |
| | HAZ | Hazardous material |
| | IDL | Inside Delivery |
| | INBD | In bond shipment |
| | IPU | Inside pickup |
| | LFTD | Lift gate required at delivery |
| | LFTP | Lift gate required at pickup |
| | LTDAD | Limited access delivery |
| | LTDAP | Limited access pickup |
| | LV1 | Project MABD Service - Level 1 -Specific for ODFL use only |
| | LV2 | Project MABD Service - Level 2 -Specific for ODFL use only |
| | MARK | Marked or tagged |
| | MNC | Must notify consignee |
| | OVR | Over dimension/excessive length |
| | PLJ | Pallet Jack Required for Delivery - Delivering Soon -Specific for ODFL use only |
| | PLU | Pallet Jack Required for Pickup - Delivering Soon -Specific for ODFL use only |
| | PPD | Perishables (food) |
| | PSC | Protective from cold |
| | PSH | Protective from heat |
| | PSN | Poisonous material |
| | REP | Residential pickup |
| | RES | Residential delivery |
| | SRT | Sort and segregate |

| Field Name | Valid Values | Description |
|---|--------------|---|
| | SS | Single Shipment |
| | TCS | Time Critical Service |
| accessorials.cod.currency, | USD | United States |
| accessorials.fullValueCoverageDetails.currency, | CAD | Canada |
| shipmentTotals.currency, shipmentTotals.currency, | MXN | Mexico -OD currently does not support MXN currency |
| customsBroker.type | Import | Customs broker handling the destination - side of the cross-border freight move |
| | Export | Customs broker handling the origin side of the cross-border freight move |

Response

Fields

| Field | Definition | Data Type |
|---|---|-----------|
| success | Successful HTTP requests. | flag |
| version | Version of the Digital LTL Council BOL. | string |
| transactionDate | The date and time for the response received YYYY-MM-DDTHH:mm:ss.sss | string |
| referenceNumbers.pro | The PRO number submitted with or generated by the request. | string |
| referenceNumbers. shipmentConfirmationNumber | Number provided by the carrier to acknowledge they accepted the BOL. - ODFL will return null | string |
| scac | 4-letter, Standard Carrier Alpha Code - ODFL | string |
| images.bol | A base 64 encoded pdf of the bill of lading. | string |
| images.shippingLabels | A base 64 encoded pdf of the shipping label. | string |
| termsAndConditions | Carrier's terms and conditions ODFL will return null | string |
| messageStatus.status | Indicates the status of the request. (See Response Values) | string |
| messageStatus.resolution | Number given to reference when requesting assistance for review. | string |
| messageStatus.messages | Message given with specific error codes. | string |

| Field | Definition | Data Type |
|---------------------------|---|-----------|
| success | Successful HTTP requests. | flag |
| version | Version of the Digital LTL Council BOL. | string |
| transactionDate | The date and time for the response received YYYY-MM-DDTHH:mm:ss.sss | string |
| messageStatus.codes | Error code given for failed request. | string |
| messageStatus.information | The code, type, and message of the response. - ODFL will return an empty list - "information": [] | list |
| resultStatusCodes | Numerical codes describing any logical status outcomes. (See Response <u>Values</u>) - Delivering Soon | string |

Flags

| Code | Message | Notes |
|------|-----------------------|---|
| 200 | ОК | Successful HTTP requests. |
| 400 | Bad Request | Often errors within the request. If the problem persists, contact API@odfl.com. |
| 401 | Unauthorized | The authentication token is missing or expired. |
| 404 | Not Found | Base Path is incorrect. |
| 500 | Internal Server Error | If the problem persists, contact API@odfl.com. |

Values

| Field Name | Values | Description |
|-------------------------------------|---------|--|
| | PASS | Request is successful with no exceptions. |
| messageStatus.status | FAIL | Request is unsuccessful due to some exception. |
| | WARNING | Request is successful with some exception. |
| | 100 | General Information |
| | 200 | Warning Non-Critical Error |
| | 300 | Failure Data Error |
| resultStatusCodes - Delivering Soon | 400 | Failure Formatting Error |
| 3 *** | 500 | Failure Business Logic Error |
| | 600 | Failure Carrier Specific Error |
| | 700 | Failure Outside Ship Window |

| Field Name | Values | Description |
|------------|--------|---|
| | 800 | Failure No Freight - Will be re-attempted |
| | 900 | Failure No Freight - Pick UP Closed |
| | 1000 | Failure Freight Not ready |
| | 1100 | Failure Packaging Problem |
| | 1200 | Failure BoL PDF Image Not Created |
| | 1300 | Failure Label PDF Image not Created |
| | 1400 | Failure Duplicate Pro |
| | 1500 | Failure Unknown Reason |
| | 1600 | Failure Shipper Closed |
| | 1700 | Failure Duplicate PO |

Sample

Request

```
"bol": {
   "function": "Create",
   "requestedPickupDate": "2025-08-27T10:30:00.000",
   "isTest": false,
   "requestorRole": "Third Party",
   "specialInstructions": "Gate code 123 to enter."
},
"version": "2.1.0",
"commodities": {
   "lineItemLayout": "nested",
   "handlingUnits": [
      {
         "count": 2,
        "type": "SKD",
"weight": 400,
         "weightUnit": "Pounds",
         "length": 48,
         "width": 48,
         "height": 48,
         "dimensionsUnit": "inches",
         "stackable": false,
         "lineItems": [
              "weight": 400,
              "classification": "85",
"description": "HAZMAT",
              "hazardous": true,
              "pieces": 1,
              "packagingType": "DRM",
```

```
"nmfc": "",
            "nmfcSub": "",
            "hazardousDescription": "UN1993, flammable liquids, n.o.s. (flammable liquids), 3, PG III",
            "hazardousDetails": {
               "weight": 50,
               "class": "3",
               "unnaNumber": "UN1993",
               "propername": " flammable liquids, n.o.s.",
               "technicalName": "flammable liquids",
               "packingGroup": "III",
               "contractNumber": "test"
            }
          }
       ]
    },
       "count": 1,
       "type": "SKD",
       "weight": 500,
       "lineItems": [
             "weight": 75,
            "classification": "92.5",
            "description": "test desc",
            "hazardous": false,
            "pieces": 10,
            "packagingType": "BOX"
             "weight": 425,
            "nmfc": "174610",
            "nmfcSub": "03",
            "classification": "250",
            "description": "test desc",
            "hazardous": false,
            "pieces": 10,
            "packagingType": "BOX"
"payment": {
  "terms": "Prepaid"
"origin": {
  "name": "Shipper Inc",
  "address1": "C/O Distribution Center",
  "address2": "123 Shipper Street",
  "city": "DOWNEY",
  "stateProvince": "CA",
  "postalCode": "90241",
  "country": "USA",
  "contact": {
     "phone": "1234569874"
"destination": {
  "name": "Consignee Co",
  "address1": "321 Consignee Court",
  "city": "Acheson",
```

```
"stateProvince": "AB",
   "postalCode": "T7X5A6",
   "country": "CAN",
   "contact": {
      "phone": "1234569874"
"billTo": {
   "account": null,
   "name": "Shipper Inc Prepaid",
   "address1": "123 Shipper Street",
   "address2": "Building 2",
   "city": "Downey",
   "stateProvince": "CA",
   "postalCode": "90241",
   "country": "USA",
   "contact": {
    "phone": "1234569874",
      "phoneExt": "6",
      "name": "Con Tact",
      "email": "test@ebol.com"
   }
},
"images": {
   "includeBol": true,
   "includeShippingLabels": true,
   "shippingLabels": {
      "format": "Avery",
      "quantity": 4,
      "position": 1
   },
   "email": {
     "includeBol": true,
      "includeLabels": true,
      "addresses": [
        "test@ebol.com"
   }
notifications": [
      "phoneNumber": "1234569874",
      "email": "test@ebol.com"
   }
"referenceNumbers": {
   "pro": "11111111111"
   "quoteId": "12345678",
   "trailerID": "1111",
   "manifestId": "2222",
   "shipmentId": "3333",
   "masterBol": "4444",
   "bol": [
      "BOL123",
      "8888888"
   "po": [
        "number": "PO123456",
        "pieces": 1,
        "weight": 400,
```

```
"weightUnit": "",
        "palletized": true,
        "additionalShipperInfo": "test"
        "number": "PO654321",
        "pieces": 10
     }
  ],
   "additionalReferences": [
        "name": "Customer",
        "value": "CustomerName"
     },
{
        "name": "Integration",
        "value": "IntegrationName"
     },
        "name": "TMS",
        "value": "TMSName"
        "name": "3PL",
        "value": "ThirdPartyLogisticsName"
     },
     {
        "name": "LOAD",
        "value": "12345"
  ]
"shipmentTotals": {
  "grossWeight": 1300,
  "netWeight": 1300,
  "weightUnit": "pounds",
  "handlingUnits": 3,
  "linearLength": 8,
  "dimensionsUnit": "inches",
  "cube": 50,
  "cubeDimensionsUnit": "feet",
  "declaredValue": 1500.20,
  "currency": "USD"
},
"accessorials": {
   "codes": [
     "HAZ",
     "FVC",
     "MARK",
     "TCS",
     "APTP"
     "APTD"
   "hazardousDetails": {
     "emergencyContact": {
        "name": "Name",
"phone": 1111111111
     }
   "fullValueCoverageDetails": {
     "monetaryValue": "500.50",
```

```
"currency": "USD"
  "markDetails": {
     "pieces": 4
  "timeCriticalDetails": {
     "type": "Delivery Window",
     "date": {
        "start": "2025-01-17T10:30:00.000",
        "end": "2025-01-17T15:30:00.000"
     }
   "appointmentDetails": {
     "pickup": {
        "start": "2025-01-15",
        "end": "2025-01-15"
     },
"delivery": {
        "start": "2025-01-17T10:30:00.000"
  }
"customsBroker": {
  "type": "Import",
  "name": "Broker LLC",
  "address1": "C/O Broker",
  "address2": "987 Broker Road",
  "city": "Atlanta",
  "stateProvince": "GA",
  "postalCode": "30304",
  "country": "USA",
  "contact": {
     "phone": "1234569874",
     "phoneExt": "2",
     "name": "Bro Ker",
     "email": "test@ebol.com"
  }
}
```

Response

```
// JSON Successful Response Data

{
    "version": "2.1.0",
    "transactionDate": "2024-10-22T13:05:40.342",
    "referenceNumbers": {
        "pro": 7777777777,
        "shipmentConfirmationNumber": null
    },
    "images": {
        "bol": null,
        "shippingLabels": null
    },
    "termsAndConditions": null,
    "messageStatus": {
```

```
"status": "PASS",
     "resolution": null,
     "message": "",
     "code": "",
     "information": []
  }
}
// JSON Response Data with Validation Errors
  "version": "2.1.0",
  "transactionDate": "2024-10-22T13:04:07.842",
  "referenceNumbers": null,
  "images": null,
  "termsAndConditions": null,
  "messageStatus": {
     "status": "FAIL",
     "resolution": "Reference number for the request is 1234567891011",
     "message": "invalid accessorials.codes. See API documentation for valid values.",
     "code": "400",
     "information": []
}
// JSON Response Data with HTML error code
{
  "timestamp": "2024-08-21T18:16:46.980+00:00",
  "status": 400,
  "error": "Bad Request",
  "path": "/bol-external-per-standards"
}
// JSON Response Data with Base Path error code
  "timestamp": "2024-08-21T18:17:16.048+00:00",
  "status": 404,
  "error": "Not Found",
  "path": "/bol-external-per-standards"
```